



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/002,333

11/14/2001

David Emerson

42390.P12368

3313

7590

04/23/2007

John P. Ward, Esq.

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

Seventh Floor

12400 Wilshire Boulevard

Los Angeles, CA 90025-1026

EXAMINER

NGUYEN, PHUONGCHAU BA

ART UNIT

PAPER NUMBER

2616

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
--	-----------	---------------

3 MONTHS

04/23/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

<b>Office Action Summary</b>	Application No. 10/002,333	Applicant(s) EMERSON ET AL.	
	Examiner Phuongchau Ba Nguyen	Art Unit 2616	

**– The MAILING DATE of this communication appears on the cover sheet with the correspondence address –  
Period for Reply**

**A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.**

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 1-22-7.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-16 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-16 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 14 November 2001 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
     Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
     Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |  |
|--|--|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                                   | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152)            |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____   |

*Claim Rejections – 35 USC § 102*

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this

Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 1–16 are rejected under 35 U.S.C. 102(e) as being anticipated by Sugar (US 2002/0061031 A1).

**Regarding claim 1:**

Sugar discloses System and Methods for Interference Mitigation among Multiple WLAN Protocol. According to Sugar, Asynchronous Connectionless (ACL) carries asynchronous data (e.g., for file transfer). ACL packets are 1, 3 or 5 slots in duration.

*identifying data for transmission* (a Multiple Protocol Communication Device-MPD functions as a Bluetooth master to exchange data with other slave terminals. The

Art Unit: 2616

MPD identifies data with a largest multi-slot packet (1, 3 or 5 slots) for transmission in order to achieve the highest throughput efficiency, see 0082, 0092-0094);

*determining how many time-slots are available for the transmission* (the MPD transmits 5-slot ACL packet in the 5-slots duration of the even-numbered timeslots that are the available timeslots for downlink data transmission to the slaves, see 0079 & 0093-0094); *and*

*upon determining the number of the available timeslots, identifying a plurality of data packet types (1, 3 or 5 slots packet-type) that fit into the available time slots and meet a minimum transfer length requirement* (if a 5-slot packet cannot be found for achieving the highest throughput efficiency, a single or a triple slot packets-minimum length requirement for transmitting are considered, see 0093-0095);

*selecting, from the identified data packets types (1, 3 or 5 slots packet-type), a data packet to transmit a portion of the data in accordance with characteristic of the transmission* (see 0093-0095)

**Regarding claim 2:**

Sugar further discloses *the identifying the data packet includes identifying a data packet type (a largest multi-slot packet) from the identified data packets types (1, 3 or 5 slots packet-type) which can be transmitted in a largest portion of the data within the time-slots available* (even-numbered downlink slots) (the MPD identifies the largest

multi-slot packet (1, 3 or 5 slots) for transmission in even-numbered downlink timeslots to achieve the highest throughput efficiency, see 0094).

**Regarding claim 3:**

Sugar further discloses *wherein the data includes at least a minimum amount of data required by the data packet type* (if a largest multi-slot packet, 5-slot packet, for achieving the highest throughput efficiency, cannot be found, a single or a triple slot packets are considered as a minimum amount of the ACL data in order to be transmitted, see 0093-0095).

**Regarding claim 4:**

Sugar further discloses *identifying a data packet type* (a largest or shortest multi-slot packet) *from the identified data packets types (1, 3 or 5 slots packet-type of ACL data packets) to transmit all the data* (if the largest multi-slot packet (5 slots) found, the largest multi-slot packet of ACL data packets is transmitted by the MPD, and if the largest multi-slot packet is not found, a shortest multi-slot packet known as a single or a triple slot packets of the ACL data packets will be transmitted, see 0093-0095 & 0141-0143).

Art Unit: 2616

**Regarding claim 7:**

In Sugar, MPD 12-fig.2 is a laptop computer augmented with the appropriate hardware and/or software, in which the hardware should include a memory for storing instructions to perform various steps. In other words, Sugar's software product stored on a processor readable memory causes the processor to perform the below steps, see 0039 & 0046 (*corresponding to a computer-readable medium having stored thereon a set of instructions to translate instructions, the set of instructions, which when executed by a processor, cause the processor to perform a method comprising*)

*identifying data for transmission* (a Multiple Protocol Communication Device-MPD functions as a Bluetooth master to exchange data with other slave terminals. The MPD identifies data with a largest multi-slot packet (1, 3 or 5 slots) for transmission in order to achieve the highest throughput efficiency, see 0082, 0092-0094);

*determining how many time-slots are available for the transmission* (the MPD transmits 5-slot ACL packet in the 5-slots duration of the even-numbered timeslots that are the available timeslots for downlink data transmission to the slaves from the MPD, see 0079 & 0093-0094); *and*

*upon determining the number of the available timeslots, identifying a plurality of data packet types (1, 3 or 5 slots packet-type) that fit into the available time slots and meet a minimum transfer length requirement* (if a 5-slot packet cannot be found for achieving the highest throughput efficiency, a single or a triple slot packets-minimum length requirement for transmitting are considered, see 0093-0095);

*selecting, from the identified data packets types (1, 3 or 5 slots packet-type), a data packet type to transmit a portion of the data in accordance with characteristic of the transmission (see 0093-0095)*

**Regarding claim 8:**

Sugar's processor readable memory causes the processor to perform the below step, *wherein the identifying the data packet includes identifying a data packet type (a largest multi-slot packet) from the identified data packets types (1, 3 or 5 slots packet-type) which can be transmitted in a largest portion of the data within the time-slots available (even-numbered downlink slots) (the MPD identifies the largest multi-slot packet (5 slots) for transmission in even-numbered downlink timeslots to achieve the highest throughput efficiency, see 0094).*

**Regarding claim 9:**

Sugar's processor readable memory causes the process to perform the below step, *wherein the data includes at least a minimum amount of data required by the data packet type (if a largest multi-slot packet, 5-slot packet, for achieving the highest throughput efficiency, cannot be found, a single or a triple slot packets are considered as a minimum amount of the ACL data in order to be transmitted, see 0093-0095).*

**Regarding claim 10:**

Sugar's processor readable memory causes the process to perform the below step for *identifying a data packet type* (a largest or shortest multi-slot packet) *from a plurality of data packets types (1, 3 or 5 slots packet-type of ACL data packets) to transmit all the data* (if the largest multi-slot packet (5 slots) found, the largest multi-slot packet of ACL data packets is transmitted by the MPD, and if the largest multi-slot packet is not found, a shortest multi-slot packet known as a single or a triple slot packets of the ACL data packets will be transmitted, see 0093-0095 & 0141-0143).

**Regarding claim 13:**

In Sugar, MPD 12-fig.2 is a laptop computer augmented with the appropriate hardware and/or software, in which the hardware should include a memory for storing instructions to perform various algorithms (*programmable modules*). In other words, Sugar's software product stored on a processor readable memory causes the processor to perform the below steps, see 0039 & 0046 (corresponding to *a computer-readable medium having stored thereon a set of instructions to translate instructions, the set of instructions, which when executed by a processor, cause the processor to perform a method comprising*)

(1) *identifying data for transmission* (a Multiple Protocol Communication Device-MPD functions as a Bluetooth master to exchange data with other slave terminals. The



MPD identifies data with a largest multi-slot packet (1, 3 or 5 slots) for transmission in order to achieve the highest throughput efficiency, see 0082, 0092-0094);

*(2) determining how many time-slots are available for the transmission (the MPD transmits 5-slot ACL packet in the 5-slots duration of the even-numbered timeslots that are the available timeslots for downlink data transmission to the slaves from the MPD, see 0079 & 0093-0094); and*

*(3) upon determining the number of the available timeslots, identifying a plurality of data packet types (1, 3 or 5 slots packet-type) that fit into the available time slots and meet a minimum transfer length requirement (if a 5-slot packet cannot be found for achieving the highest throughput efficiency, a single or a triple slot packets-minimum length requirement for transmitting are considered, see 0093-0095) and to select, from the identified data packets types (1, 3 or 5 slots packet-type), a data packet type to transmit a portion of the data (if a 5-slot packet, for achieving the highest throughput efficiency, cannot be found, a single or a triple slot packets are considered as portion of the ACL data to be transmitted, see 0093-0095).*

**Regarding claim 14:**

Sugar further discloses MPD 12-fig.1 is a Bluetooth master device functioning as a hub or router to transmit data packets to slaves, see 0039 (corresponding to *wherein the computing system includes a computer network router*).

**Regarding claims 5, 11, and 15:**

As to claim 5, Sugar discloses the step of identifying the data packet that includes identifying a data packet from the identified data packets *types (1, 3 or 5 slots packet-type)* which is least error prone packets (Sugar, page 5, paragraph 0059, wherein Sugar determines the bit error rate (BER.) of each packet to be transmitted. The packet with lowest BER will be least error prone).

As to claims 11 and 15, claims 11 and 15 recite substantially similar limitations and are similarly analyzed.

**Regarding claim 6,**

Sugar discloses a method comprising:

*identifying data for transmission* (a Multiple Protocol Communication Device-MPD functions as a Bluetooth master to exchange data with other slave terminals. The MPD identifies data with a largest multi-slot packet (1, 3 or 5 slots) for transmission in order to achieve the highest throughput efficiency, see 0082, 0092-0094);

*determining how many time-slots are available for the transmission (the MPD transmits 5-slot ACL packet in the 5-slots duration of the even-numbered timeslots that are the available timeslots for downlink data transmission to the slaves, see 0079 & 0093-0094); and*

*upon determining the number of the available timeslots, identifying a plurality of data packet types (1, 3 or 5 slots packet-type) that fit into the available time slots and meet a minimum transfer length requirement (if a 5-slot packet cannot be found for achieving the highest throughput efficiency, a single or a triple slot packets-minimum length requirement for transmitting are considered, see 0093-0095) and can be transmitted in a transmitter logic lower power mode (wherein 0096 disclosed that the transmission of MPD preventing the received signal energy reflected from the transmitted BT signal from interfering with the 802.11 receiver, thus the packet was selected for transmitting at a lower level power in order to prevent interference with the 802.11 receiver, see also 0092); and*

*selecting, from the identified data packet types, a data packet type to transmit a portion of the data in accordance with characteristics of the transmission (after knowing that the packets available for transmitting only fit into the 3 slots instead of 5 slots, the 3 slots would be selected for transmission, thus the number of packet available for transmission determining the type of slots for transmitting-emphasis added, see 0093-0095).*

Art Unit: 2616

**Regarding claim 12,**

In Sugar, MPD 12-fig.2 is a laptop computer augmented with the appropriate hardware and/or software, in which the hardware should include a memory for storing instructions to perform various steps. In other words, Sugar's software product stored on a processor readable memory causes the processor to perform the below steps, see 0039 & 0046 (corresponding to *a computer-readable medium having stored thereon a set of instructions, which when executed by a processor, cause the processor to perform a method comprising*)

*identifying data for transmission* (a Multiple Protocol Communication Device-MPD functions as a Bluetooth master to exchange data with other slave terminals. The MPD identifies data with a largest multi-slot packet (1, 3 or 5 slots) for transmission in order to achieve the highest throughput efficiency, see 0082, 0092-0094);

*determining how many time-slots are available for the transmission* (the MPD transmits 5-slot ACL packet in the 5-slots duration of the even-numbered timeslots that are the available timeslots for downlink data transmission to the slaves from the MPD, see 0079 & 0093-0094); *and*

*upon determining the number of the available timeslots, identifying a plurality of data packet types (1, 3 or 5 slots packet-type) that fit into the available time slots and meet a minimum transfer length requirement* (if a 5-slot packet cannot be found for achieving the highest throughput efficiency, a single or a triple slot packets-minimum length requirement for transmitting are considered, see 0093-0095) *and can be*

Art Unit: 2616

*transmitted in a transmitter logic lower power mode (wherein 0096 disclosed that the transmission of MPD preventing the received signal energy reflected from the transmitted BT signal from interfering with the 802.11 receiver, thus the packet was selected for transmitting at a lower level power in order to prevent interference with the 802.11 receiver, see also 0092); and*

*selecting, from the identified data packet types, a data packet type to transmit a portion of the data in accordance with characteristics of the transmission (after knowing that the packets available for transmitting only fit into the 3 slots instead of 5 slots, the 3 slots would be selected for transmission, thus the number of packet available for transmission determining the type of slots for transmitting-emphasis added, see 0093-0095).*

**Regarding claim 16,**

In Sugar, MPD 12-fig.2 is a laptop computer augmented with the appropriate hardware and/or software, in which the hardware should include a memory for storing instructions to perform various algorithms (*programmable modules*). In other words, Sugar's software product stored on a processor readable memory causes the processor to perform the below steps, see 0039 & 004616 (corresponding to *a computing system comprising*):

*identifying data for transmission* (a Multiple Protocol Communication Device-MPD functions as a Bluetooth master to exchange data with other slave terminals. The MPD identifies data with a largest multi-slot packet (1, 3 or 5 slots) for transmission in order to achieve the highest throughput efficiency, see 0082, 0092-0094);

*determining how many time-slots are available for the transmission* (the MPD transmits 5-slot ACL packet in the 5-slots duration of the even-numbered timeslots that are the available timeslots for downlink data transmission to the slaves from the MPD, see 0079 & 0093-0094); *and*

*upon determining the number of the available timeslots, identifying a plurality of data packet types (1, 3 or 5 slots packet-type) that fit into the available time slots and meet a minimum transfer length requirement* (if a 5-slot packet cannot be found for achieving the highest throughput efficiency, a single or a triple slot packets-minimum length requirement for transmitting are considered, see 0093-0095) *and can be transmitted in a transmitter logic lower power mode* (wherein 0096 disclosed that the transmission of MPD preventing the received signal energy reflected from the transmitted BT signal from interfering with the 802.11 receiver, thus the packet was selected for transmitting at a lower level power in order to prevent interference with the 802.11 receiver, see also 0092); *and*

*selecting, from the identified data packet types, a data packet type to transmit a portion of the data in accordance with characteristics of the transmission* (after knowing that the packets available for transmitting only fit into the 3 slots instead of 5 slots, the 3

*slots would be selected for transmission, thus the number of packet available for transmission determining the type of slots for transmitting-emphasis added, see 0093-0095).*

3. Claims 5, 11, 15 are rejected under 35 U.S.C. 102(e) as being anticipated by Mansfield (US 6,704,346).

Mansfield discloses identifying data for transmission, determining how many time slots are available and identifying a plurality of data packets that fit into the available time-slots and are of a data packet type, See col. 6, lines 29-36, which is least prone to a transmission error (DMI instead of DH1 packet usage), See col.15, lines 11-50. Note: The claim merely states that the packet least prone to error is identified. In Bluetooth, DM and DH identification is inherent (FEC and without FEC respectively).

#### ***Response to Arguments***

4. Applicant's arguments filed 1-22-7 have been fully considered but they are not persuasive.

A/. In the Remarks, page 8, Applicant argued that Sugar does not teach determining how many timeslot are available for transmission data, then

identifies data packets types that fit into the available timeslot and meet a minimum transfer length requirement.

In reply, Applicant admitted that Sugar allowed the MPD to use 5-slot packets to achieve the highest throughput efficiency (i.e., minimum for using the 5-slot packet is 1 slot packet usage—emphasis added, see 0093–0095).

And if less than 5 packets are available the MPD transmits single or triple-slot packets. Thus, the 5-slot packet type met a number of timeslots available, only the packets that were identified in the slot availability would be accepted (i.e., 1, 3 or 5 slots packet types; page 7, 0082). Normally, 5-slot packets would be used for transmission, but upon the determining of the characteristics of the transmission, only 3-slot packets would be transmitted, thus identifying 3-slots in duration for transmission, emphasis added.

6. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Phuongchau Ba Nguyen whose telephone number is 571–272–3148. The examiner can normally be reached on Monday–Friday from 10:00 a.m. to 6:00 p.m..



If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Huy Vu can be reached on 571-272-3155. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

  
Phuongchau Ba Nguyen  
Examiner  
Art Unit 2616

  
HUY D. VU  
SUPERVISORY PATENT EXAMINER  
TECHNOLOGY CENTER 2600